BR-1

CO_2 Confetti Blaster

Single-outlet confetti effects for clubs and live events.



Product rendering

50 W

RATED POWER

7–8 m

APPROX. JET RANGE

100 m²

COVERAGE

CO_2 confetti effects

Single-outlet confetti output

CO_2 rapidly projects large volumes of confetti.
For clubs and live events.

Range & coverage

Approx. 7–8 m jet range.
Coverage of 100 m².

Compact, durable body

Sturdy housing with convenient installation.

Valve & control

Premium low-temperature valve set.
Electrical and DMX512 control.



Confetti effect illustration

Power, output & control

Electrical & performance

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Fuse	**2 A**
Rated power	**50 W**
Max. jet range	**Approx. 7–8 m**
Coverage	**100 m²**

Control & triggering

PARAMETER	SPECIFICATION
DMX512	**Supported**
DMX channels	**2**
Wireless remote	**Not supported**
Effect LEDs	**None**
Triggering	**Electrical / DMX512**

Jet range and coverage may vary with operating conditions.

CO_2 system & transport

CO_2 system

PARAMETER	SPECIFICATION
Gas type	**CO_2 gas**
Valves	**Low-temperature valve set**
Construction	**Compact, durable body**
Output	**Single outlet**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**560 × 300 × 310 mm**
Carton dimensions	**625 × 365 × 375 mm**
Net weight	**7.8 kg**
Gross weight	**9.8 kg**

Format & applications

FEATURE	SPECIFICATION
Format	**CO_2 -powered confetti blaster**
Applications	**Clubs / live events**
Effect	**High-volume confetti output**