CF-3

Compact Natural Haze Generator

Fine haze for smaller indoor and outdoor spaces.



Product rendering

1,150 W

RATED POWER

100 m²/min

APPROX. MAX. COVERAGE

3 L

FLUID TANK

Haze production & control

Linear fine-haze output

Control output via DMX512
or a wireless remote.

Efficient heating & uniform haze

Intelligent gas/fluid mixing creates uniform haze
with broad coverage and long hang time.

Quiet, long-throw airflow

Ultra-quiet fan supports smaller indoor venues.

Maintenance & consumption

Intelligent automatic cleaning
with low gas and fluid consumption.



Haze effect illustration

Power, output & control

Electrical & performance

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Fuse	**10 A / 250 V**
Rated power	**1,150 W**
Warm-up time	**Approx. 7.5 min**
Max. coverage	**Approx. 100 m²/min**

Control & maintenance

PARAMETER	SPECIFICATION
Output adjustment	**Linear**
DMX512	**Supported**
DMX channels	**2**
Wireless remote	**Supported**
Automatic cleaning	**Intelligent**

Results may vary with operating conditions.

Consumables & transport

Fluid & gas

PARAMETER	SPECIFICATION
Fluid tank	**3 L**
Gas cylinder	**Optional**
Haze fluid	**F-C1 optical haze fluid**
Drive gas	**CO_2 or nitrogen (N_2)**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**505 × 335 × 330 mm**
Carton dimensions	**592 × 417 × 400 mm**
Net weight	**13.5 kg**
Gross weight	**16.5 kg**

Fluid & gas consumption

OPERATING PARAMETER	CONSUMPTION
Haze fluid at 1% output	**Approx. 1.5 mL/min**
Haze fluid at 100% output	**Approx. 7 mL/min**
Gas consumption	**Approx. 0.6 kg/h**