CV-2

Dual-Head CO_2 Jet

Dual CO_2 effects for major venues and live shows.



Product rendering

50 W
RATED POWER

10 m
MAX. JET RANGE

6.7 kg
NET WEIGHT

CO_2 jet effects & control

Dual CO_2 output

Dual-head output for major venues.
Maximum jet range of 10 m.

Suspended or stand-mounted

Housing designed for suspended setups
or secure stand mounting.

Nozzle & valve design

Noise-reducing multi-hole nozzles.

Control & signal stability

Electrical triggering and DMX512 operation.
Interference-resistant control circuitry.



Dual CO_2 effect illustration

Power, jet & control

Electrical & jet system

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Fuse	**5 A**
Rated power	**50 W**
Max. jet range	**10 m**
Jet heads	**Dual**

Control & triggering

PARAMETER	SPECIFICATION
DMX512	**Supported**
DMX channels	**1**
Wireless remote	**Not supported**
Effect LEDs	**None**
Triggering	**Electrical / DMX512**

Results may vary with operating conditions.

CO_2 system & transport

CO_2 system

PARAMETER	SPECIFICATION
Gas type	**Food-grade CO_2**
Valves	**Cryogenic-rated solenoids**
Nozzles	**Noise-reducing, multi-hole**
Gas flow	**Precision metering**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit incl. bracket	**350 × 310 × 320 mm**
Carton dimensions	**420 × 370 × 425 mm**
Net weight	**6.7 kg**
Gross weight	**8.5 kg**

Jet format & application

FEATURE	SPECIFICATION
Jet format	**Dual CO_2 output**
Placement	**Suspended / stand-mounted**
Applications	**Major venues / live shows**