CY-500

Mini Fog Machine

Light fog for karaoke rooms and small clubs.



Product rendering

500 W

RATED POWER

35 s

WARM-UP TIME

1.5 L

FOG FLUID TANK

Light fog for small venues

Compact housing & quiet fan

The quiet fan produces a light, dry fog effect.
Suited to karaoke rooms and small clubs.

Wide-bore stainless steel heater

The wide flow path helps resist clogging.
Temperature control regulates the heater.

Adjustable fog & airflow

Set the fog output and airflow for the room.

DMX512 & wireless remote

Two DMX channels for console control.
Wireless remote control is supported.



Karaoke lounge fog illustration

Power, fog output & control

Electrical & fog output

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Rated power	**500 W**
Fuse	**5 A / 250 V**
Warm-up time	**35 s**
Fog output	**Approx. 4,000 cu ft/min**

Control & fluid use

PARAMETER	SPECIFICATION
DMX512	**Supported**
DMX channels	**2**
Wireless remote	**Supported**
Fog & airflow	**Adjustable**
Fluid consumption	**Approx. 3.5 mL/min**

Fog output and fluid use are approximate. Results vary with operating conditions.

Fluid, mounting & packing

Fluid & mounting

PARAMETER	SPECIFICATION
Fog fluid tank	**1.5 L**
Consumable	**FY-1 entertainment fog fluid**
Mounting	**Adjustable bracket**
Fan	**Quiet airflow**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**280 × 190 × 260 mm**
Dimension basis	**Includes mounting bracket**
Net weight	**2.8 kg**
Gross weight	**3.1 kg**

Packaging

PACK CONFIGURATION	DIMENSIONS
Single-unit carton	**343 × 263 × 280 mm**
Four-unit carton	**540 × 355 × 570 mm**
Dimensions	**Millimetres**