FV-30

Rainproof LED Fog Jet

Colourful fog columns for indoor and outdoor stages.



Product rendering

3,000 W

RATED POWER

15 m

APPROX. JET DISTANCE

5 L

FLUID TANK

LED fog effects & control

Airflow-assisted fog columns

Fast start/stop bursts with a jet distance of approximately 15 m.

Rapid pressure recovery

Dual-pipe output and integrated plumbing support repeat bursts and reduce leaks.

28 × 8 W RGBW LEDs

High-brightness LEDs colour the fog output.

Indoor / outdoor flexibility

IPX3 rain resistance and multi-angle mounting. DMX512 and wireless remote control.



Fog effect illustration

Power, output & control

Electrical & performance

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Fuse	**20 A**
Rated power	**3,000 W**
Warm-up time	**6.5 min**
Fog output	**Approx. 120,000 ft³/min**

LED & control

PARAMETER	SPECIFICATION
LED power	**28 × 8 W**
LED colour	**RGBW**
DMX512	**Supported**
DMX channels	**10 / 11**
Wireless remote	**Supported**

Results may vary with operating conditions.

Consumables & transport

Fluid & output

PARAMETER	SPECIFICATION
Fluid tank	**5 L**
Fluid type	**FR-1 high-density fog fluid**
Fluid consumption	**2 min / 1 L**
Jet distance	**Approx. 15 m**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**554 × 371 × 343 mm**
Carton dimensions	**645 × 455 × 420 mm**
Net weight	**27 kg**
Gross weight	**30 kg**

Installation & construction

FEATURE	SPECIFICATION
Rain resistance	**IPX3**
Installation	**Flexible multi-angle mounting**
Fog system	**Dual pipe with integrated plumbing**