FV-35

Rainproof LED Fog Jet

Vivid fog columns for live stages and events.



Product rendering

3,000 W

RATED POWER

15 m

APPROX. JET DISTANCE

6 L

FLUID TANK

LED fog effects & control

Airflow-assisted fog columns

Instant fog columns reach approximately 15 m with constant-pressure technology.

Rapid pressure recovery

Dual-channel output and integrated piping support repeat bursts and reduce leaks.

28 × 8 W RGBW LEDs

High-brightness LEDs colour the fog output.

Integrated 6 L reservoir

Durable built-in tank and IPX3 housing. DMX512 and wireless remote control.



Fog effect illustration

Power, output & control

Electrical & performance

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Fuse	**20 A**
Rated power	**3,000 W**
Warm-up time	**6.5 min**
Fog output	**Approx. 120,000 ft³/min**

LED & control

PARAMETER	SPECIFICATION
LED power	**28 × 8 W**
LED colour	**RGBW**
DMX512	**Supported**
DMX channels	**10 / 11**
Wireless remote	**Supported**

Results may vary with operating conditions.

Consumables & transport

Fluid & output

PARAMETER	SPECIFICATION
Fluid tank	**6 L**
Fluid type	**FR-1 high-density fog fluid**
Fluid consumption	**2 min / 1 L**
Jet distance	**Approx. 15 m**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**506 × 371 × 340 mm**
Carton dimensions	**590 × 455 × 420 mm**
Net weight	**30 kg**
Gross weight	**33 kg**

Integrated fluid system

FEATURE	SPECIFICATION
Rain resistance	**IPX3**
Reservoir	**Durable built-in 6 L tank**
Fog system	**Dual channel with integrated piping**