FZ-1500

Professional Entertainment Hazer

Fine, dry haze for large clubs and live performances.



Product rendering

1,500 W

RATED POWER

9,000 ft³/min

APPROX. FOG OUTPUT

4 L

FLUID TANK

Haze production & control

Light, dry haze

Smooth, fine haze without burnt odour
for large clubs and live performances.

Heater & temperature control

Clog-resistant stainless steel heater with
precise temperature monitoring.

Independent haze & fan control

Adjust haze output and fan speed separately.

Protection & signal stability

Protection against operation without fluid.
High immunity to signal interference.



Haze effect illustration

Power, output & control

Electrical & performance

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Fuse	**10 A / 250 V**
Rated power	**1,500 W**
Warm-up time	**40 s**
Fog output	**Approx. 9,000 ft³/min**

Control & operation

PARAMETER	SPECIFICATION
Output adjustment	**Independent haze / fan**
DMX512	**Supported**
DMX channels	**2**
Wireless remote	**Supported**
Temperature control	**Precise monitoring**

Results may vary with operating conditions.

Consumables & transport

Fluid system

PARAMETER	SPECIFICATION
Fluid tank	**4 L**
Fluid type	**FY-1 entertainment fog fluid**
Fluid consumption	**8 mL/min**
Fluid path	**Clog-resistant stainless steel**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**340 × 305 × 295 mm**
Carton dimensions	**420 × 370 × 370 mm**
Net weight	**8 kg**
Gross weight	**9.7 kg**

Protection & output control

FEATURE	SPECIFICATION
Fluid protection	**Dry-running protection**
Fan control	**Independent linear adjustment**
Signal stability	**High interference immunity**