HZ-1500

Stage Lighting Hazer

Soft, fine haze for stage beam effects and touring.



Product rendering

1,200 W

RATED POWER

10,000 ft³/min

APPROX. FOG OUTPUT

9.5 L

FLUID TANK

Haze production & control

Immediate haze without heating

Soft, fine haze starts instantly
with no warm-up delay.

Multi-stage output system

Boosted drive system increases haze output
for atmospheric stage-lighting effects.

Quiet, long-throw airflow

High-speed turbine fan with adjustable outlet.

Touring case & control

9.5 L reservoir and bilingual LCD.
DMX512, wireless remote and soft case corners.



Haze effect illustration

Power, output & control

Electrical & performance

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Fuse	**10 A / 250 V**
Rated power	**1,200 W**
Warm-up time	**0 s**
Fog output	**Approx. 10,000 ft³/min**

Control & airflow

PARAMETER	SPECIFICATION
Fan system	**High-speed turbine fan**
DMX512	**Supported**
DMX channels	**2**
Wireless remote	**Supported**
Outlet direction	**Adjustable**

Results may vary with operating conditions.

Consumables & transport

Fluid system

PARAMETER	SPECIFICATION
Fluid tank	**9.5 L**
Fluid type	**HZL-A optical haze fluid**
Fluid consumption	**Approx. 3 mL/min**
Output character	**Soft, fine haze**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**690 × 515 × 615 mm**
Carton dimensions	**710 × 535 × 630 mm**
Net weight	**68 kg**
Gross weight	**70 kg**

Touring case & display

FEATURE	SPECIFICATION
Drive system	**Multi-stage boosted output**
LCD	**Chinese / English**
Flight case	**Protective soft corners**



Closed flight case rendering