HZ-1

Professional Air-Atomising Hazer

Immediate fine haze for indoor and outdoor shows.



Product rendering

600 W

RATED POWER

5,400 ft³/min

APPROX. FOG OUTPUT

3 L

FLUID TANK

Haze production & control

Immediate haze without heating

Compressed-air atomisation starts output without a preheating cycle.

Light, dry haze

Continuous fine haze with wide coverage for extended performances.

Adjustable airflow & direction

Variable fan speed and adjustable outlet angle.

Power & signal stability

Long-life integrated power system with high electrical interference resistance.



Haze effect illustration

Power, output & control

Electrical & performance

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Fuse	**5 A / 250 V**
Rated power	**600 W**
Warm-up time	**0 s**
Fog output	**Approx. 5,400 ft³/min**

Control & airflow

PARAMETER	SPECIFICATION
Airflow adjustment	**Variable fan speed**
DMX512	**Supported**
DMX channels	**2**
Wireless remote	**Supported**
Outlet angle	**Adjustable**

Results may vary with operating conditions.

Consumables & transport

Fluid & atomisation

PARAMETER	SPECIFICATION
Fluid tank	**3 L**
Fluid type	**HZL-A optical haze fluid**
Fluid endurance	**Approx. 10 h/L**
Atomisation	**Compressed air**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit incl. casters	**520 × 385 × 435 mm**
Carton dimensions	**530 × 400 × 440 mm**
Net weight	**30.7 kg**
Gross weight	**31.8 kg**

Power system & output

FEATURE	SPECIFICATION
Power system	**Integrated, long-life**
Haze character	**Light, dry haze**
Signal stability	**High electrical interference resistance**