IPD-1500

Rain-Resistant Fog Machine

Outdoor fog with a separate fluid reservoir.



Product rendering

1,500 W

RATED POWER

IPX3

RAIN RESISTANCE

3 L

EXTERNAL FLUID TANK

Fog effects for outdoor shows

IPX3 rain-resistant housing

The housing uses corrosion-resistant panels.
For festivals and outdoor attractions.

External 3 L reservoir

The separate tank provides access for refills.
A supplied 10 m hose connects it to the unit.

Compact scenic mounting

The yoke supports mounting on scenic structures.

DMX512 & wireless remote

One DMX channel for console control.
Wireless remote operation is supported.



Outdoor stage fog illustration

Power, fog output & control

Electrical & fog output

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Rated power	**1,500 W**
Fuse	**10 A**
Warm-up time	**4 min**
Fog output	**Approx. 23,000 cu ft/min**

Control & fluid use

PARAMETER	SPECIFICATION
DMX512	**Supported**
DMX channels	**1**
Wireless remote	**Supported**
Rain resistance	**IPX3**
Fluid consumption	**6 min/L**

Fog output is approximate. Results vary with operating conditions.

Fluid system, size & mounting

External fluid system

PARAMETER	SPECIFICATION
Tank capacity	**3 L**
Tank placement	**External reservoir**
Supplied fluid hose	**10 m**
Consumable	**FG-1 high-density effect fluid**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**365 × 395 × 252 mm**
Net weight	**8.5 kg**
Gross weight	**11 kg**
Packing dimensions	**Unspecified**

Installation features

FEATURE	DETAIL
Mounting yoke	**Supports scenic and architectural mounting.**
External tank	**Separate placement gives access for refills.**
Housing panels	**Corrosion-resistant construction.**