PO-1

Rainbow Bubble Machine

Dense bubble effects for shows and attractions.



Product rendering

100 W	Approx. 4 m	0 s
RATED POWER	BUBBLE THROW	WARM-UP TIME

Twin-outlet bubble effects

High-volume bubble output

Produces a dense stream of bubbles.
For commercial shows, attractions and events.

Independent outlet adjustment

Adjust the two fan outlets independently.
Approx. 4 m bubble throw.

Corrosion-resistant housing

Molded plastic body with a water-resistant motor.

Wireless remote & optional DMX

Wireless remote operation is supported.
One DMX channel on the custom DMX512 option.



Garden venue bubble effect illustration

Power, bubble throw & control

Electrical & bubble output

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Rated power	**100 W**
Fuse	**10 A / 250 V**
Warm-up time	**0 s**
Bubble throw	**Approx. 4 m**

Control & fluid use

PARAMETER	SPECIFICATION
Wireless remote	**Supported**
DMX512	**Custom option**
DMX channels	**1 (DMX512 option)**
Outlet adjustment	**Independent**
Fluid consumption	**100 min/L**

Bubble throw is approximate. Results vary with operating conditions.

Bubble fluid, size & construction

Bubble fluid system

PARAMETER	SPECIFICATION
Tank capacity	**2.5 (unit not specified)**
Consumable	**PO-1 bubble fluid**
Fluid consumption	**100 min/L**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**430 × 350 × 350 mm**
Net weight	**6.2 kg**
Gross weight	**8.5 kg**
Packing dimensions	**Unspecified**

Construction

FEATURE	DETAIL
Housing	**Corrosion-resistant molded plastic.**
Motor	**Water-resistant construction.**
Top carry handle	**For transport between setups.**