QV-2

LED Fog Jet

RGB fog jets for clubs and stage performances.



Product rendering

1,700 W

RATED POWER

6–8 m

APPROX. JET DISTANCE

3 L

FLUID TANK

RGB fog effects & control

Precision high-energy heater

Rugged compact design with stable fog jets.
Approx. 32,000 ft³/min fog output.

32 × 3 W RGB LEDs

High-brightness LEDs add rich colour
to the fog column.

Fast cut-off & fluid protection

Rapid fog stop with dry-running protection.

Mounting & remote control

Adjustable bracket for hanging or mounting.
DMX512 and wireless remote operation.



Fog effect illustration

Power, output & control

Electrical & performance

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Fuse	**10 A / 250 V**
Rated power	**1,700 W**
Warm-up time	**4.5 min**
Fog output	**Approx. 32,000 ft³/min**

LED & control

PARAMETER	SPECIFICATION
LED power	**32 × 3 W**
LED colour	**RGB**
DMX512	**Supported**
DMX channels	**8**
Wireless remote	**Supported**

Results may vary with operating conditions.

Consumables & transport

Fluid & output

PARAMETER	SPECIFICATION
Fluid tank	**3 L**
Fluid type	**FV-1 fast-dissipating jet fluid**
Fluid consumption	**180 mL/min**
Jet distance	**Approx. 6–8 m**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**403 × 353 × 255 mm**
Carton dimensions	**470 × 400 × 315 mm**
Net weight	**9.2 kg**
Gross weight	**11.75 kg**

Protection & installation

FEATURE	SPECIFICATION
Fluid protection	**Dry-running protection**
Mounting	**Adjustable hanging / mounting bracket**
Fog control	**Rapid cut-off**