WS-2000

Compact Low-Lying Fog Machine

Water-based ground fog for weddings and small venues.



Product rendering

1,500 W	≈ 200 m²	7.5 L
RATED POWER	MAX. COVERAGE	WATER TANK

Low-lying fog for small venues

Fog that hugs the floor

The water-based module produces a low fog layer.
Suited to first dances, parties and private events.

Compact housing & extension hose

The housing resists corrosion.
A telescopic hose directs fog along the floor.

Output & trigger control

Adjust fog volume and set timed output.

Water level & drainage

A window shows the water level during filling.
A quick drain simplifies emptying the tank.



Wedding reception fog illustration

Power, fog output & control

Electrical & fog output

PARAMETER	SPECIFICATION
Input voltage	**AC 220–240 V, 50/60 Hz**
Rated power	**1,500 W**
Fuse	**8 A**
Warm-up time	**Approx. 2 min**
Max. fog output	**Approx. 13,000 cu ft/min**

Coverage & control

PARAMETER	SPECIFICATION
Max. coverage	**Approx. 200 m²**
DMX512	**Supported**
Channel count	**2 or 3**
Wireless remote	**Supported**
Trigger modes	**DMX / electrical / manual**

Output and coverage are approximate. Results vary with operating conditions.

Tanks, dimensions & transport

Water & fog fluid

PARAMETER	SPECIFICATION
Water tank	**7.5 L**
Fog fluid tank	**2.2 L**
Max. fluid use	**Approx. 18 mL/min**
Consumables	**FL-1 or FG-1 fluid + water**

Dimensions & weight

PARAMETER	SPECIFICATION
Unit dimensions	**470 × 305 × 325 mm**
Packing dimensions	**750 × 355 × 380 mm**
Net weight	**14.5 kg**
Gross weight	**19 kg**

Setup features

FEATURE	FUNCTION
Extension hose	**Positions the floor outlet away from the housing.**
Water level window	**Shows the fill level in the water tank.**
Quick drain	**Lets the operator empty the water tank.**